

McGUIRE

A Division of Systems, LLC

CENTRAAIR® SERIES

AIR POWERED LEVELER



CentraAir® Series, 6' x 8', 45,000 CIR, Shown patent pending

- ▶ Easy push button activation or lanyard control for smooth, consistent operation with an air powered system that provides for full float at all positions.
- ▶ Reduces electrical footprint
- ▶ Powered from plant air system or dedicated compressor
- ▶ Automatic lip extension with yieldable lip
- ▶ Below dock end load capability
- ▶ Full width rear hinge mounted in compression with structural channel support
- ▶ Proven industrial air bellow technology
- ▶ Low maintenance design
- ▶ Integral maintenance strut is lockout/tagout compliant with lip support strut that also allows convenient servicing of the lip
- ▶ Installed RFL air lubricator to operate in cold weather
- ▶ Made in the USA

GENERAL DESCRIPTION: All McGuire® CentraAir® (CA) Series dock levelers incorporate the use of common plant air combined with an industrial automotive grade air bellows system to raise and lower the platform. Systems, LLC is an active member of Loading Dock Equipment Manufacturers (LODEM), a product section of the Material Handling Industry. Unit conforms to OSHA, U.S. Department of Commerce Standard CS-202-56 and is manufactured in compliance with the American National Standard of Safety Performance and Testing of Dock Leveling Devices (ANSI) MH 30.1. Unit manufactured by McGuire.

OPERATION: The CentraAir Series Leveler is available with "push button" activation either electrical or pneumatic, or lanyard control. With either system, the activation of the CA Leveler is simple. The dock attendant either pushes and holds the raise button or pulls and holds the lanyard at the rear of ramp, unit will raise and lip will extend. Releasing either the raise button or lanyard will permit the leveler to float down to the bed of the truck. Service range is from 12" above to 12" below dock level. Lip keepers welded to frame members provide nighttime security and cross-traffic support. Full operating range toe guards are provided as standard. Maintenance prop with 'Lock-out Tag-out' capability is provided as standard.

CONSTRUCTION: The platform is constructed of 1/4" thick 4-way high tensile 50,000 minimum yield A572 safety tread plate. Platform is reinforced and supported by full length 6" height "C" channels for 25,000 lb CIR to 40,000 lb CIR units, full length 6" height structural channel for 45,000 lb CIR units and full length 6" height structural channel and I beams for 55,000 lb CIR units, all welded to deck for firm structural support. Front and rear header plate is 1/2" thick x 7" high hot rolled steel. McGuire CA series lips are 4-way safety tread plate, the 25,000 lb CIR is 1/2" thick and the 30,000, 35,000, 40,000, lb CIR are 5/8" thick and the 45,000 lb, 55,000 lb CIR units are 3/4" thick. The standard lip length is 16" on all capacities. Hinge tubes are 1 3/4" OD x 5/16" wall, 1 7/8" OD x 3/8" wall or 2 1/8" OD x 1/2" wall depending on CIR. All lip hinge pins are 1" diameter M1044 steel. Steel header gussets are standard on all models 35,000 lb CIR and above. All units have grease fittings as standard. All platforms are designed to compensate for up to 4" of canted trailer bed.

INSTALLATION: Unit shipped completely assembled and ready for installation in preformed concrete pit. Pit construction to be in accordance with certified McGuire pit detail drawings. Contact McGuire for current cost and nearest distributor.

SAFETY EQUIPMENT: Pivoting cross traffic legs of solid steel bar construction provide multi position safety at dock level and below. Self contained lip control yields under impact from incoming trailer. Leveler is equipped with built-in maintenance prop with "Lockout/Tagout" capability; full range toe guards and night lock security. Unit can be equipped with an optional STOP-TITE®, TPR®, or TPR® UniLock series vehicle restraint devices or Light Communication System signs and lights.

COLORS: Levelers painted slate blue. Other colors are available. Consult factory.

DOCK BUMPERS: Two black laminated 4" thick x 10"H x 14"W standard. Optional sizes and types are available.

VEHICLE RESTRAINT SYSTEMS: McGuire CentraAir Series air powered levelers can be equipped with an optional STOP-TITE, TPR, or TPR UniLock series vehicle restraint or the Light Communication System to help prevent unexpected trailer departure from the loading dock and minimize trailer creep during the loading/unloading process and to enhance communication at the dock area.

ELECTRICAL: The CentraAir Series Dock Leveler operates off existing plant air regulated at approximately 90 psi or off a dedicated compressor. Activation of the unit is either push button or lanyard control. Lanyard control is located at the back of the leveler, similar to a mechanical unit and requires no electrical for the unit, making it a ideal for electrically starved areas or explosion proof applications. The "push button" option utilizes a 115V circuit to power an extremely low amp (.073 amp) solenoid which activates the system. Both push button and lanyard models incorporate a 5 ft² industrial automotive grade bellows system, which exhausts air through a cartridge valve located in the pit. Please Note: Unless specifically noted on quotation, all electrical requirements are the responsibility of others.

WARRANTY: All McGuire CentraAir Series models feature a full one (1) year base warranty on all structural, pneumatic and electrical parts, including freight and labor charges in accordance with McGuire's Standard Warranty Policy. Lifting system, including industrial air bellows, mounting brackets, cartridge valves and seals an additional full four (4) year warranty on parts. Structural components carry an additional four (4) year pro-rated warranty. McGuire warrants all components to be free of defects in materials and workmanship, under normal use, during the warranty period. This base warranty period begins upon the completion of installation or the sixtieth (60th) day after shipment, whichever is earlier. Additional warranty extensions may be available upon approved submittal of application information.

DOCK LEVELER



A Division of Systems, LLC

CENTRAIR® SERIES

AIR POWERED LEVELER

Optional Equipment for CA Series Air Powered Leveler

Check Options Desired

- | | |
|------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|
| <input type="checkbox"/> 18" Lip | <input type="checkbox"/> Special color _____ |
| <input type="checkbox"/> 20" Lip | <input type="checkbox"/> Yellow and black toe guard safety tape |
| <input type="checkbox"/> Rubber weather seal | <input type="checkbox"/> Laminated bumpers |
| <input type="checkbox"/> Brush weather seal | <input type="checkbox"/> B410-14 (horizontal) |
| <input type="checkbox"/> 3 wheel fork truck protection (standard on 45,000 & 50,000 CIR units) | <input type="checkbox"/> VB420-11 (vertical) |
| <input type="checkbox"/> iDock® Controls (with interlock capability) | <input type="checkbox"/> VB424-11 (vertical) |
| <input type="checkbox"/> Integrated control panel | <input type="checkbox"/> 6" thick dock bumpers |
| <input type="checkbox"/> Operation | <input type="checkbox"/> Steel faced |
| <input type="checkbox"/> Electrical Push Button | <input type="checkbox"/> TPR® restraint |
| <input type="checkbox"/> Pneumatic Push Button | <input type="checkbox"/> TPR UniLock® restraint |
| <input type="checkbox"/> Lanyard Control | <input type="checkbox"/> STOP-TITE® restraint (manual) |
| <input type="checkbox"/> 5" high standard safety barrier lip | <input type="checkbox"/> STOP-TITE® restraint (automatic) |
| <input type="checkbox"/> Pit steel (6 piece curb angle set) | <input type="checkbox"/> iDock® Alert Communication System |
| <input type="checkbox"/> Pit steel (4 angle/2 bumper) | <input type="checkbox"/> Wheel chocks model # _____ |
| <input type="checkbox"/> Pit kit (3 sided) | <input type="checkbox"/> Dock light (no bulb) model # _____ |
| <input type="checkbox"/> Pan unit (4 sided) | <input type="checkbox"/> _____ |
| <input type="checkbox"/> Foam insulation | <input type="checkbox"/> _____ |
| | <input type="checkbox"/> _____ |

Dimensions and Capacities

Select a Model and a Capacity

| CA MODEL - NOMINAL SIZE | CAPACITY-COMPARATIVE INDUSTRY RATING (CIR) |
|---------------------------------------------|--------------------------------------------|
| <input type="checkbox"/> CA-66 6' x 6' | <input type="checkbox"/> 25,000 LBS. CIR |
| <input type="checkbox"/> CA-68 6' x 8' | <input type="checkbox"/> 30,000 LBS. CIR |
| <input type="checkbox"/> CA-610 6' x 10' | <input type="checkbox"/> 35,000 LBS. CIR |
| <input type="checkbox"/> CA-656 6'6" x 6' | <input type="checkbox"/> 40,000 LBS. CIR |
| <input type="checkbox"/> CA-658 6'6" x 8' | <input type="checkbox"/> 45,000 LBS. CIR |
| <input type="checkbox"/> CA-6510 6'6" x 10' | <input type="checkbox"/> 55,000 LBS. CIR |
| <input type="checkbox"/> CA-76 7' x 6' | |
| <input type="checkbox"/> CA-78 7' x 8' | |
| <input type="checkbox"/> CA-710 7' x 10' | |

Customer: _____
 Job: _____
 Location: _____
 Number of Units: _____
 Model: _____
 Voltage/Phase: _____
 Represented By: _____
 Sales Rep: _____

Certified for Construction:
 By: _____
 Title: _____
 Date: _____
 Company: _____
 City: _____
 State: _____

SS CA 2/22

Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.

McGuire • Division of Systems, LLC • W194 N11481 McCormick Dr. • P.O. Box 309 • Germantown, WI 53022
Phone: 800.624.8473 • Email: sales@wbmcguire.com • www.wbmcguire.com

DOCK LEVELER