

# HP Series Hydraulic Leveler

## Specification Sheet & Submittal

25K - 40K  
CIR

6' - 7'  
WIDTH

6' - 10'  
LENGTH



### Standard Features

Easy push-button operation for smooth, consistent operation with a hydraulic system that provides for full float at all positions

Positive lip extension and retraction with true regenerative hydraulic control

Safety yellow full-range toe guards

Structural C and I beam deck supports (45K and above)

Velocity fuse hydraulic fail safe stops platform within 1" to 3" in free fall situation

B410-14 laminated dock bumpers

### Construction

The platform is constructed of  $\frac{1}{4}$ " thick 4-way high strength, low alloy 50,000 minimum yield A572 safety tread plate. Platform is reinforced and supported by full length 6" height "C" channels welded to deck and front and rear header plate is  $\frac{1}{2}$ " thick x 7" high hot rolled steel. McGuire HP series lips are 4-way safety tread plate, the 25,000 lb CIR is  $\frac{1}{2}$ " thick, or the 30,000, 35,000 and 40,000 lb CIR are  $\frac{5}{8}$ " thick. The standard lip length is 16" on all capacities. Hinge tubes are 1  $\frac{3}{4}$ " OD x 5/16" wall, 1 7/8" OD x 3/8" wall or 2 1/8" OD x  $\frac{1}{2}$ " wall depending on CIR. All lip hinge pins are 1" diameter M1044 steel. Steel header gussets are standard on all models 35,000 lb CIR and above. All units have grease fittings as standard. All platforms are designed to compensate for up to 4" of canted trailer bed.

### Operation

The HP Series Lever is controlled remotely from a wall mounted control panel. An array of optional control panel features are available. Service range is from 12" above to 12" below dock level. Lip keepers welded to frame members provide night time security and cross-traffic support. Full operating range toe guards are provided as standard. Maintenance strut with lockout/tagout capability is provided as standard. Factory finish includes rust inhibitive coat industrial grade finish. Special coating and colors are optional.

### Hydraulics

Platform is raised by a main hydraulic cylinder; all hydraulic hoses are routed under the leveler platform, away from debris. Hoist cylinder is a hard chrome-plated double acting design with a 3" ID bore. Main cylinder is equipped with a velocity safety stop to limit free fall of a loaded platform to 3" (+/- 1"). Lip operation is controlled by a hard chrome plated cylinder having a 2" ID bore and is fully yieldable. Motor pump is mounted up for easy access and to clear debris in pit. Reservoir is translucent for monitoring of fluid level.

## Electrical

Hydraulic pump motor either 1.25 HP TENV at 120v or 208v, single phase or at 208v, 230v, 460v, or 575v three phase. All electrical components, connections and wiring are UL listed or recognized. **Please Note:** Unless specifically noted on quotation, all electrical requirements are the responsibility of others.

## Safety Equipment

Standard non-adjustable hydraulic velocity fuse limits platform free fall to 3" (+/- 1") with heavy load on platform. Full range telescoping toe guards close off leveler sides even in highest upward position. Lip keepers are cross traffic support and serve as automatic night lock security against break in attempts. Built in maintenance inspection strut that is lockout/tagout compliant is included. HP series can be equipped with UniChock™, UXL, STOP-TITE®, TPR®, or TPR® UniLock series vehicle restraint devices or Light Communication System signs and lights.

## Colors

Levelers painted slate blue. Other colors are available. Consult factory.

## Dock Bumpers

Two black laminated 4" thick x 10" H x 14" W bumpers as standard. Optional sizes and types are available.

## Vehicle Restraint Systems

McGuire HP Series hydraulic levelers can be equipped with UniChock, UXL, STOP-TITE, TPR, or TPR UniLock series vehicle restraint or a Light Communication System to help prevent unexpected trailer departure from the loading dock and minimize trailer creep during the loading/unloading process and to enhance communication at the dock area.

## Warranty

All McGuire HP Series models feature a full one (1) year base warranty on all structural, hydraulic and electrical parts, including freight and labor charges in accordance with McGuire's standard warranty policy. Structural and hydraulic components carry an additional full four (4) year pro-rated warranty. McGuire warrants all components to be free of defects in materials and workmanship, under normal use, during the warranty period. This base warranty period begins upon the completion of installation or the sixtieth (60th) day after shipment, whichever is earlier. Additional warranty extensions may be available upon approved submittal of application information.

## Order Specifications

### Dimensions and Capacities

#### Select a Model and a Capacity

MODEL	NOMINAL SIZE	CIR (Comparative Industry Rating)
<input type="checkbox"/> HP-66	6' x 6'	<input type="checkbox"/> 25,000 CIR
<input type="checkbox"/> HP-68	6' x 8'	<input type="checkbox"/> 30,000 CIR
<input type="checkbox"/> HP-610	6' x 10'	<input type="checkbox"/> 35,000 CIR
<input type="checkbox"/> HP-656	6'6" x 6'	<input type="checkbox"/> 40,000 CIR
<input type="checkbox"/> HP-658	6'6" x 8'	
<input type="checkbox"/> HP-6510	6'6" x 10'	
<input type="checkbox"/> HP-76	7' x 6'	
<input type="checkbox"/> HP-78	7' x 8'	
<input type="checkbox"/> HP-710	7' x 10'	

#### Check Options Desired

### Optional Equipment

- 18" Lip
- 20" Lip
- Auto Return to Dock
- Rubber Weather Seal
- Brush Weather Seal
- 3-Wheel Fork Truck Protection
- Lip Extend Only Button
- Mushroom-Style E-Stop Button
- Light Communication System
- Dock Alert (NEMA12)
- iDock 1.0 Alert
- iDock 2.0 Alert
- Integrated Control Panel
- 5" High Standard Safety Barrier Lip
- Pit Steel (6-piece curb angle set)
- Pit Steel (4 angle/2 bumper)
- Pit Kit (3 sided)
- Pan Unit (4 sided)
- Foam Insulation
- Special Color \_\_\_\_\_
- Yellow and Black Toe Guard Safety Tape
- Laminated Bumpers
  - B410-14 (horizontal)
  - VB420-11 (vertical)
  - VB424-11 (vertical)
  - 6" Thick Dock Bumpers
  - Steel Faced
- TPR® Restraint
- TPR® UniLock Restraint
- STOP-TITE® Manual Restraint
- STOP-TITE® Automatic Restraint
- UniChock™ Restraint
- UXL Restraint
- Wheel Chocks Model# \_\_\_\_\_
- Dock Light (no bulb) Model # \_\_\_\_\_

## Required Information

CUSTOMER	
JOB	
LOCATION	
NUMBER OF UNITS	
MODEL	
VOLTAGE/PHASE	
REPRESENTED BY	
SALES REP	

## Certified for Construction

BY	
TITLE	
DATE	
COMPANY	
CITY & STATE	