

Wheel-Based Vehicle Restraint



FEATURES

- Universal wheel chock with light communication system
- Audible alerts to ensure safe use and storage
- Interior messages for the position of the chock
- iDock® Alert with dynamic message display
- Strong grip to limit sliding
- Aluminum for strength and lightweight
- Zinc-plated steel teeth and storage bracket
- Replaceable teeth for overall longevity
- iDock 2.0 Controls connected online with optional myQ® Enterprise
- Designed and manufactured in the USA

Connect online
with

myQ®
Enterprise

** UniChock sample installation. Product subject to change. iDock Controls shown with optional dock light push button.*

UniChock™

Wheel-Based Vehicle Restraint

VEHICLE RESTRAINT SYSTEM

The UniChock™ is a wheel-based trailer restraint with advanced light communication and available as a standalone unit or integrated with other dock equipment. Universally effective in most conditions, the unit helps prevent unexpected trailer departure or movement from the loading dock during the loading process.

OPERATION

Once a trailer is fully backed and parked in position against the dock bumpers, the yellow UniChock is removed from the storage bracket and placed under the front of one of the trailer's back tires. A message will display on the iDock® Controller that the unit is in a safe position. The dock attendant can then proceed to open the door and deploy the leveler.

After loading is complete, the dock attendant stores the leveler and closes the overhead door, either of which must have an installed switch interlocked with the restraint. This will then sound and display indications to return the UniChock™ to the storage bracket.

SAFETY FEATURES

- Damaged traction teeth can be replaced as necessary to maintain a stronger grip
- Automatic light sequencing with interior/exterior red/green lights always in opposition
- Exterior and interior audible alarms if the UniChock is not in a safe position during loading
- Full communication package with lights, signs and control panel with universal signage pictures for additional communication safety
- Optional integrated iDock Controls for safe leveler interlock



Secure grip to the ground with audible indicators if in unsafe position during loading.

LIGHT COMMUNICATION

The UniChock uses advanced iDock Controls with an LED 3-color light communication system. As a truck approaches, the exterior light is green and the interior light is red. Once a trailer is parked at the dock and the UniChock is correctly positioned under the trailer's tire, the exterior light automatically changes to red and interior light to green. If the chock is moved to an unsafe position during loading, an audible alarm will sound and the interior light will change to alternating red and amber until the restraint is back in the correct position.

CONSTRUCTION & ELECTRICAL

The restraint unit is durable and light weight aluminum with a powder coat finish. The traction teeth and storage bracket are zinc-plated steel. Wired sensors are installed in the restraint unit and the storage bracket. The control panel is NEMA 4X with all components, connections and wiring UL listed and/or recognized. Panels are built in-house in a UL-approved control panel shop.

myQ®
Enterprise

CONNECTIVITY

iDock 2.0 Controls come standard and ready to connect online.



UNICHOCK™

COMMON OPTIONS

Bracket extension for alternative storage positions
Connect online with myQ Enterprise
Custom interlock sequence with leveler and/or door
Integrated control panel

W194N11481 McCormick Dr. | Germantown, WI 53022
wbmcguire.com | sales@wbmcguire.com
800-624-8473



wbmcguire.com

Designed, Engineered, and Manufactured in the U.S.A.
© 2026 Systems, LLC/McGuire
Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.



A Division of Systems, LLC